

Order Code: XCSF80NWW

80W - High Output Slim Floodlight - IP65 - 4000K - White

**Features**

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 81 lumens per watt efficacy

Construction

- White or black body finish
- Breather gland for reducing condensation

**Technical Data****General**

Luminaire Wattage (W)	80
Weight (kg)	4.80
Operating Temperature (ta °C)	-20 to 25

Light Output

Lumens (lm)	6500
Efficacy (lm/W)	81

LED

CCT (K)	4000
CRI	65
Macadam Ellipses	4

Electrical

Rated Input Current (A)	0.35
Power Factor (pf)	0.9
Input Voltage Range (VAC)	100-240
Inrush Current Peak (A)	120
Surge Protection (kV)	1
Conductor Size (mm)	1.5
Terminal Type	3 pole screw down

Order Code: XCSF80NWW

80W - High Output Slim Floodlight - IP65 - 4000K - White

Dimensions

A (mm)	415
B (mm)	310
C (mm)	88

Line Drawing

