# xcite LED Lighting

## **Data Sheet**



0.039

25

220 - 240

0.5 to 2.5

3 pole screw down

Order Code: XCSH7WWW 7W - Shaver Light - 3000K - White





- Suitable for bathrooms zone 3 where no water jet is likely to be used
- Pull cord switch
- Shaver socket with dual voltage selector switch
- Continuous power allowing shaver use when not illuminated

#### Construction

Supplied as standard with warm white [3000K] LED

#### **Installation Notes**

Fixed via base plate Wired via 3-pole terminal connection inside main body













### **Technical Data**

General		Electrical
Luminaire Wattage (W)	7	Rated Input Current (A)
Weight (kg)	0.70	Power Factor (pf)
Operating Temperature (ta °C)	-10 to 40	Input Voltage Range (VAC)
Light Output		Inrush Current Peak (A)
Light Output Lumens (lm)	600	Conductor Size (mm)
Efficacy (Im/W)	86	Terminal Type
LED		
CCT (K)	3000	
CRI	80	
Macadam Elipses	<4	
Driver		
Driver Current (mA)	350mA	
Forward Voltage (V)	10.4 - 12.8	



# xcite LED Lighting

## **Data Sheet**



Order Code: XCSH7WWW 7W - Shaver Light - 3000K - White

#### **Dimensions**

A (mm)	500
B (mm)	50
C (mm)	60

### Line Drawing



