

Order Code: XCSH7WWW
7W - Shaver Light - 3000K - White



Features

- Suitable for bathrooms zone 3 where no water jet is likely to be used
- Pull cord switch
- Shaver socket with dual voltage selector switch
- Continuous power allowing shaver use when not illuminated

Construction

- Supplied as standard with warm white [3000K] LED

Installation Notes

Fixed via base plate
Wired via 3-pole terminal connection inside main body



Technical Data

General		Electrical	
Luminaire Wattage (W)	7	Rated Input Current (A)	0.039
Weight (kg)	0.70	Power Factor (pf)	0.7
Operating Temperature (ta °C)	-10 to 40	Input Voltage Range (VAC)	220 - 240
Light Output		Inrush Current Peak (A)	25
Lumens (lm)	600	Conductor Size (mm)	0.5 to 2.5
Efficacy (lm/W)	86	Terminal Type	3 pole screw down
LED			
CCT (K)	3000		
CRI	80		
Macadam Ellipses	<4		
Driver			
Driver Current (mA)	350mA		
Forward Voltage (V)	10.4 - 12.8		

Order Code: XCSH7WWW
7W - Shaver Light - 3000K - White

Dimensions

A (mm)	500
B (mm)	50
C (mm)	60

Line Drawing

