

**Order Code: XCSL433NWM3**

33W - Surface module - Fixed output - Emergency - 4000K



**Features**

- Suitable for schools, corridors and general areas
- Available in 2 lengths and 2 outputs
- Surface mounted

**Construction**

- Steel body in white finish
- Opal polycarbonate diffuser
- Rear BESA fixings or side cable entry
- Supplied as standard with neutral white [4000K] LED



**Technical Data**

**General**

Luminaire Wattage (W)	33
Weight (kg)	2.10
Operating Temperature (ta °C)	5 to 25

**Light Output**

Lumens (lm)	3900
Efficacy (lm/W)	118

**LED**

CCT (K)	4000
CRI	80
Macadam Elipses	<3

**Driver**

Driver Current (mA)	700
Forward Voltage (V)	41

**Emergency**

Emergency Lumen Operating	290
---------------------------	-----

**Electrical**

Rated Input Current (A)	0.15
Power Factor (pf)	0.95
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	80
Surge Protection (kV)	2
Conductor Size (mm)	0.5 to 2.5
Terminal Type	3-POLE GRIP-WIRE

**Order Code:** XCSL433NWM3

33W - Surface module - Fixed output - Emergency - 4000K

Dimensions

A (mm)	1203
B (mm)	154
C (mm)	70

Line Drawing

