

Order Code: XCSSL4X1M3MS

XCITE Surface Linear X1 - White - 3000K-5000K + Wattage Switchable - Opal diffuser - Microwave sensor



Features

- **23, 29, 35, 40 wattage options**
Allows the output to be matched to the lighting requirements of the space.
- **Low glare TP[a] diffuser**
Improves visual comfort and helps create a more productive working environment
- **3000K, 4000K and 5000K selectable**
Enables the lighting colour to be tailored to suit different environments and user preferences
- **120 lm/W efficacy**
Delivers high performance illumination while helping to reduce energy consumption and running costs

Construction

- **Rear and end cable entry points**
Allows flexible installation options to simplify wiring and reduce installation time
- **Microwave sensor option available**
Supports additional energy savings through automatic occupancy based lighting control
- **Emergency option available**
Maintains illumination during mains power failure to support safe evacuation of the building

Technical Data

General

| | |
|-------------------------------|----------------|
| Luminaire Wattage (W) | 23, 29, 35, 40 |
| Weight (kg) | 2.74 |
| Operating Temperature (ta °C) | 5° to 25° |

Light Output

| | |
|-----------------|---------------------|
| Lumens (lm) | 2600/3300/3900/4500 |
| Efficacy (lm/W) | 113 |

LED

| | |
|------------------|-------------|
| CRI | 83 to 87 |
| Macadam Ellipses | 3.1 to 10.1 |

Driver

| | |
|---------------------|------------|
| Driver Current (mA) | 200 to 350 |
| Forward Voltage (V) | 103 to 108 |

Emergency

| | |
|---------------------------|-----|
| Emergency Lumen Operating | 283 |
| Emergency Wattage (W) | 3 |

Electrical

| | |
|---------------------------|-------------------------|
| Rated Input Current (A) | 0.11 to 0.18 |
| Power Factor (pf) | 0.9 to 0.96 |
| Input Voltage Range (VAC) | 220 to 240 |
| Inrush Current Peak (A) | 18.3 |
| Surge Protection (kV) | L to N 1KV LN to PG 2KV |
| Conductor Size (mm) | 0.5 to 2.5 |
| Terminal Type | 4 pole piano key |

Order Code: XCSL4X1M3MS

XCITE Surface Linear X1 - White - 3000K-5000K + Wattage Switchable - Opal diffuser - Microwave sensor

Dimensions

| | |
|--------|------|
| A (mm) | 1225 |
| B (mm) | 155 |
| B (mm) | 55 |

Line Drawing

