

Order Code: XCSL553NWMS

53W - Surface module - Fixed output - Microwave sensor - 4000K

**Features**

- Suitable for schools, corridors and general areas
- Available in 2 lengths and 2 outputs
- Surface mounted

Construction

- Steel body in white finish
- Opal polycarbonate diffuser
- Rear BESA fixings or side cable entry
- Supplied as standard with neutral white [4000K] LED

Technical Data**General**

Luminaire Wattage (W)	53
Weight (kg)	2.00
Operating Temperature (ta °C)	0 to 25

Light Output

Lumens (lm)	6200
Efficacy (lm/W)	117

LED

CCT (K)	4000
CRI	80
Macadam Ellipses	<3

Driver

Driver Current (mA)	1050
Forward Voltage (V)	46.5

Electrical

Rated Input Current (A)	0.24
Power Factor (pf)	0.96
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	50
Surge Protection (kV)	2
Conductor Size (mm)	0.5 to 2.5
Terminal Type	4-POLE GRIP-WIRE

Order Code: XCSL553NWMS

53W - Surface module - Fixed output - Microwave sensor - 4000K

Dimensions

A (mm)	1503
B (mm)	154
C (mm)	70

Line Drawing

