

### Order Code: XCSL5X1M3MS

XCITE Surface Linear X1 - White - 3000K-5000K + Wattage Switchable - Opal diffuser - Microwave sensor



### Features

- **28, 34, 41, 47 wattage options**  
Allows the output to be matched to the lighting requirements of the space.
- **Low glare TP[a] diffuser**  
Improves visual comfort and helps create a more productive working environment
- **3000K, 4000K and 5000K selectable**  
Enables the lighting colour to be tailored to suit different environments and user preferences
- **120 lm/W efficacy**  
Delivers high performance illumination while helping to reduce energy consumption and running costs

### Construction

- **Rear and end cable entry points**  
Allows flexible installation options to simplify wiring and reduce installation time
- **Microwave sensor option available**  
Supports additional energy savings through automatic occupancy based lighting control
- **Emergency option available**  
Maintains illumination during mains power failure to support safe evacuation of the building

### Technical Data

#### General

Luminaire Wattage (W)	28, 34, 41, 47
Weight (kg)	3.28
Operating Temperature (ta °C)	5° to 25°

#### Light Output

Lumens (lm)	3300/4100/4900/5600
Efficacy (lm/W)	118

#### LED

CRI	83 to 87
Macadam Ellipses	2.8 to 8.8

#### Driver

Driver Current (mA)	200 to 350
Forward Voltage (V)	127 to 133

#### Emergency

Emergency Lumen Operating	295
Emergency Wattage (W)	3

#### Electrical

Rated Input Current (A)	0.13 to 0.21
Power Factor (pf)	0.92 to 0.96
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	43.6
Surge Protection (kV)	L to N 1KV LN to PG 2KV
Conductor Size (mm)	0.5 to 2.5
Terminal Type	4 pole piano key

### Order Code: XCSL5X1M3MS

XCITE Surface Linear X1 - White - 3000K-5000K + Wattage Switchable - Opal diffuser - Microwave sensor

#### Dimensions

A (mm)	1525
B (mm)	155
B (mm)	55

#### Line Drawing

