

Order Code: XCTLD5CT

5W - Fire Rated Recessed Downlight - Trimless - CCTK Selector [3000K/4000K/6000K] - White



Features

- Compact fire rated downlight with trimless finish
- CCT selectable via selector switch [3000K/4000K/6000K]
- Dimmable as standard
- Concealed trim for plaster-in finish
- 30 minute fire rating with Staircraft I-Joist [\[Compatibility Matrix\]](#)
- 30, 60 & 90 minute fire rating with solid timber joists
- Up to 100 lumens per watt efficacy

Construction

- Steel body providing a high level of fire protection in accordance with Building Regulations Part B
- Loop in/out mains connections with easy-fit connector
- Integral driver



Technical Data

General

Luminaire Wattage (W)	5
Weight (kg)	0.37

Electrical

Input Voltage Range (VAC)	230
---------------------------	-----

Light Output

Lumens (lm)	400 to 500
Efficacy (lm/W)	100

LED

CCT (K)	3000K/4000K/6000K
---------	-------------------

Order Code: XCTLD5CT

5W - Fire Rated Recessed Downlight - Trimless - CCTK Selector [3000K/4000K/6000K] - White

Dimensions

C (mm)	70
-----	-----
Cut Out (mm)	95
-----	-----
Dia. (mm)	145
-----	-----

Line Drawing

