

Order Code: XCTPANM3ST

XCITE TWINSPOT ST XCTPA 2W - 6500K - Fixed output - Emergency Self-test



Features

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries for wall or ceiling fix
- High quality LED heads eliminate the need for replacement
- 2 LED heads with 54 LED SMD array
- Supplied with LiFePO4 battery

Construction

- Polycarbonate body
- Operates in non-maintained mode
- Integral auto self-test for reduced maintenance, includes a disable function

Technical Data

General		Electrical	
Luminaire Wattage (W)	2	Rated Input Current (A)	0.05
Weight (kg)	1.16	Power Factor (pf)	0.2
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
LED		Conductor Size (mm)	1.5
CRI	70	Terminal Type	3 pole piano key
Macadam Elipses	4.1		
Driver			
Driver Current (mA)	1200		
Forward Voltage (V)	3.1		
Emergency			
Emergency Lumen Operating	600		
Emergency Wattage (W)	2		

Order Code: XCTPANM3ST
XCITE TWINSPOT ST XCTPA 2W - 6500K - Fixed output - Emergency Self-test

Dimensions

A (mm)	300
B (mm)	290
C (mm)	65

Line Drawing

