xcite LED Lighting
Data Sheet

Order Code: XCUCL16WW

16W - Slimline Under Cupboard Cabinet Light - IP20 - 3000K

Features

- Ideal for replacement of linear fluorescent fixtures
- Available in 5 lengths
- Full set of connectors and accessories supplied
- Slimline profile for discreet installation
- Up to 100 lumens per watt efficacy

Construction

- Extruded plastic body
- LED SMD modules array

Technical Data

General

Luminaire Wattage (W)	16
Weight (kg)	0.26

Light Output

Lumens (lm)	1600
Efficacy (lm/W)	100

LED

CCT (K)	3000
CRI	80
Macadam Elipses	4

Electrical

Rated Input Current (A)	0.07
Power Factor (pf)	0.4
Input Voltage Range (VAC)	200-240
Inrush Current Peak (A)	15
Surge Protection (kV)	0.5
Conductor Size (mm)	0.75
Terminal Type	Bare wire

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

xcite LED Lighting

Data Sheet


Order Code: XCUCL16WW

16W - Slimline Under Cupboard Cabinet Light - IP20 - 3000K

Dimensions

Length (mm)	1157
Width (mm)	23
Depth (mm)	37

Line Drawing



Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk