

Order Code: XCUD15WWSS

5W - Decorative Wall Light - One-Way [Down] - IP54 - 3000K - Stainless steel



Features

- Decorative one-way [down] wall light suitable for domestic use
- Suitable for exterior use and walkways
- Low energy LED module for reduced running costs
- Up to 60 lumens per watt efficacy

Construction

- Die-cast aluminium body
- Supplied as standard with warm white [3000K] LED

Technical Data

| General | | Electrical | |
|-------------------------------|---------|---------------------------|-------------------|
| Luminaire Wattage (W) | 5 | Rated Input Current (A) | 0.03 |
| Weight (kg) | 0.54 | Power Factor (pf) | 0.7 |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 230 |
| Light Output | | Inrush Current Peak (A) | 15 |
| Lumens (lm) | 300 | Conductor Size (mm) | 1.5 |
| Efficacy (lm/W) | 60 | Terminal Type | 3 pole screw down |
| LED | | | |
| CCT (K) | 3000 | | |
| CRI | 80 | | |
| Macadam Elipses | 4 | | |
| Driver | | | |
| Driver Current (mA) | 300 | | |

Order Code: XCUD15WWSS
5W - Decorative Wall Light - One-Way [Down] - IP54 - 3000K - Stainless steel

Dimensions

| | |
|-----------|-----|
| A (mm) | 120 |
| B (mm) | 85 |
| Dia. (mm) | 78 |

Line Drawing

