# xcite LED Lighting

### **Data Sheet**



Order Code: XCUD210WWSS

10W - Decorative Wall Light - Up/Down - IP54 - 3000K - Stainless Steel



### **Features**

- Decorative up/down wall light suitable for domestic use
- Low energy LED module for reduced running costs
- Up to 70 lumens per watt efficacy

#### Construction

- · Die-cast aluminium body
- Supplied as standard with warm white [3000K] LED















### **Technical Data**

General		Electrical	
Luminaire Wattage (W)	10	Rated Input Current (A)	0.04
Weight (kg)	0.82	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	230
Limbs Outrook		Inrush Current Peak (A)	30
Light Output Lumens (Im)	700	Conductor Size (mm)	1.5
Efficacy (lm/W)	70	Terminal Type	3 pole screw down
LED			
CCT (K)	3000		
CRI	80		
Macadam Elipses	4		
Driver			
Driver Current (mA)	250		



# xcite LED Lighting

## Data Sheet



### Order Code: XCUD210WWSS

10W - Decorative Wall Light - Up/Down - IP54 - 3000K - Stainless Steel

#### **Dimensions**

A (mm)	163
B (mm)	85
Dia. (mm)	78

### Line Drawing



