

Order Code: XCWL23CT

23W - Wallpack CC - IP65 - CCTK Selector [3000K/4000K/6000K]



Features

- Ideal for retrofit of HID discharge wallpacks
- Suitable for exterior walls and entrance areas
- CCT selectable via 2-way dip switch [3000K/4000K/6000K]
- Sensor options available
- Up to 70 lumens per watt efficacy

Construction

- Polycarbonate body and diffuser
- Integral emergency option available
- CRI: Ra>80



Technical Data

General		Electrical	
Luminaire Wattage (W)	23	Rated Input Current (A)	0.12
Weight (kg)	1.40	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
		Inrush Current Peak (A)	10
		Surge Protection (kV)	1
		Conductor Size (mm)	2.5
		Terminal Type	3 pole piano key
Light Output			
Lumens (lm)	1600 to 1900		
Efficacy (lm/W)	70		
LED			
CCT (K)	3000K/4000K/6000K		
CRI	>80		
Macadam Elipses	4		
Driver			
Driver Current (mA)	700		
Forward Voltage (V)	25.2-30.6		

Order Code: XCWL23CT

23W - Wallpack CC - IP65 - CCTK Selector [3000K/4000K/6000K]

Dimensions

A (mm)	307
B (mm)	257
C (mm)	105

Line Drawing

