

Order Code: XCWL23NWHFS

23W - Bulkhead High Output Wall Pack - IP65 - 4000K - Microwave Sensor - 4000K



Features

- Ideal for retrofit of HID discharge wallpacks
- Suitable for exterior walls and entrance areas
- Sensor options available
- Photocell option available
- Up to 70 lumens per watt efficacy

Construction

- Polycarbonate body and diffuser
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



Technical Data

| General | | Electrical | |
|-------------------------------|---------|---------------------------|------------------|
| Luminaire Wattage (W) | 23 | Rated Input Current (A) | 0.12 |
| Weight (kg) | 1.15 | Power Factor (pf) | 0.8 |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 220-240 |
| Light Output | | Surge Protection (kV) | 1 |
| | | Conductor Size (mm) | 2.5 |
| | | Terminal Type | 3 pole piano key |
| Lumens (lm) | 1600 | | |
| Efficacy (lm/W) | 70 | | |
| LED | | | |
| CCT (K) | 4000 | | |
| CRI | 80 | | |
| Macadam Elipses | 4 | | |

Order Code: XCWL23NWHFS

23W - Bulkhead High Output Wall Pack - IP65 - 4000K - Microwave Sensor - 4000K

Dimensions

| | |
|--------|-----|
| A (mm) | 307 |
| B (mm) | 257 |
| C (mm) | 105 |

Line Drawing

