

Order Code: XCWL23NWHFSPC

23W - Bulkhead High Output Wall Pack - IP65 - 4000K - Microwave Sensor and Photocell - 4000K



Features

- Ideal for retrofit of HID discharge wallpacks
- Suitable for exterior walls and entrance areas
- Sensor options available
- Photocell option available
- Up to 70 lumens per watt efficacy

Construction

- Polycarbonate body and diffuser
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



Technical Data

General		Electrical	
Luminaire Wattage (W)	23	Rated Input Current (A)	0.12
Weight (kg)	1.30	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
		Surge Protection (kV)	1
		Conductor Size (mm)	2.5
		Terminal Type	3 pole piano key
Light Output			
Lumens (lm)	1600		
Efficacy (lm/W)	70		
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		

Order Code: XCWL23NWHFSPC

23W - Bulkhead High Output Wall Pack - IP65 - 4000K - Microwave Sensor and Photocell - 4000K

Dimensions

A (mm)	307
B (mm)	257
C (mm)	105

Line Drawing

