

Order Code: XCWL23NWM3

23W - Bulkhead High Output Wall Pack - IP65 - 4000K - 3hrs Maintained Emergency - 4000K



Features

- Ideal for retrofit of HID discharge wallpacks
- Suitable for exterior walls and entrance areas
- Sensor options available
- Photocell option available
- Up to 70 lumens per watt efficacy

Construction

- Polycarbonate body and diffuser
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



Technical Data

General

| | |
|-------------------------------|---------|
| Luminaire Wattage (W) | 23 |
| Weight (kg) | 1.35 |
| Operating Temperature (ta °C) | 5 to 25 |

Light Output

| | |
|-----------------|------|
| Lumens (lm) | 1600 |
| Efficacy (lm/W) | 70 |

LED

| | |
|-----------------|------|
| CCT (K) | 4000 |
| CRI | 80 |
| Macadam Elipses | 4 |

Emergency

| | |
|---------------------------|-----|
| Emergency Lumen Operating | 130 |
| Emergency Wattage (W) | 2 |

Electrical

| | |
|---------------------------|------------------|
| Rated Input Current (A) | 0.12 |
| Power Factor (pf) | 0.9 |
| Input Voltage Range (VAC) | 220-240 |
| Surge Protection (kV) | 1 |
| Conductor Size (mm) | 2.5 |
| Terminal Type | 4 pole piano key |

Order Code: XCWL23NWM3

23W - Bulkhead High Output Wall Pack - IP65 - 4000K - 3hrs Maintained Emergency - 4000K

Dimensions

| | |
|--------|-----|
| A (mm) | 307 |
| B (mm) | 257 |
| C (mm) | 105 |

Line Drawing

