

**Order Code: XCWL23NWPCM3**

23W - Bulkhead High Output Wall Pack - IP65 - 4000K - Photocell - 3hrs Maintained Emergency - 4000K



**Features**

- Ideal for retrofit of HID discharge wallpacks
- Suitable for exterior walls and entrance areas
- Sensor options available
- Photocell option available
- Up to 70 lumens per watt efficacy

**Construction**

- Polycarbonate body and diffuser
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



**Technical Data**

**General**

Luminaire Wattage (W)	23
Weight (kg)	1.50
Operating Temperature (ta °C)	5 to 25

**Light Output**

Lumens (lm)	1600
Efficacy (lm/W)	70

**LED**

CCT (K)	4000
CRI	80
Macadam Elipses	4

**Emergency**

Emergency Lumen Operating	130
Emergency Wattage (W)	2

**Electrical**

Rated Input Current (A)	0.12
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Surge Protection (kV)	1
Conductor Size (mm)	2.5
Terminal Type	3 pole piano key

### Order Code: XCWL23NWPCM3

23W - Bulkhead High Output Wall Pack - IP65 - 4000K - Photocell - 3hrs Maintained Emergency - 4000K

#### Dimensions

A (mm)	307
B (mm)	257
C (mm)	105

#### Line Drawing

