xcite LED Lighting
Data Sheet

Order Code: XCWL23NWPCM3

23W - Bulkhead High Output Wall Pack - IP65 - 4000K - Photocell - 3hrs Maintained Emergency - 4000K



Features

- Ideal for retrofit of HID discharge wallpacks
- Suitable for exterior walls and entrance areas
- Sensor options available
- Photocell option available
- Up to 70 lumens per watt efficacy

Construction

- Polycarbonate body and diffuser
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED

Technical Data

General

Luminaire Wattage (W)	23
Weight (kg)	1.50
Operating Temperature (ta °C)	5 to 25

Light Output

Lumens (lm)	1600
Efficacy (lm/W)	70

LED

CCT (K)	4000
CRI	80
Macadam Elipses	4

Emergency

Emergency Lumen Operating	130
Emergency Wattage (W)	2

Electrical

Rated Input Current (A)	0.12
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Surge Protection (kV)	1
Conductor Size (mm)	2.5
Terminal Type	3 pole piano key

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

xcite LED Lighting

Data Sheet

Order Code: XCWL23NWPCM3

23W - Bulkhead High Output Wall Pack - IP65 - 4000K - Photocell - 3hrs Maintained Emergency - 4000K

Dimensions

Length (mm)	307
Width (mm)	257
Depth (mm)	105

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk